



LCD-190TK

19" (48 CM) LCD MONITOR, METAL CASING,
GLASS FRONT PANEL

KEY FEATURES

- Metal casing with glass front panel
- Resolution: 1280 (H) x 1024 (V)
- Brightness: 300 cd/m²
- 4:3 aspect ratio
- 800:1 contrast ratio
- 6 ms response time
- VESA 100
- 1x BNC In, 1x BNC Out, 1x VGA
- Remote control included



The monitors from the TK Series feature a metal housing with a tempered glass protected panel for added durability. They deliver crisp clear images and offer BNC, VGA and S-Video connections making them the ideal solution for a wide variety of CCTV monitoring applications.

GENERAL SPECIFICATIONS

LCD panel type	19" (48 cm) active matrix with glass front
Max. resolution	1280 (H) x 1024 (V)
Pixel pitch	0.294 (H) x 0.294 (V)
Bezel thickness	20mm
Contrast ratio	800:1
Brightness	300 cd/m ²
Response time	6 ms
Viewing angle	75° / 75° / 75° / 75°
Display colours	16.7 millions
Video synchronisation	TTL positive or negative
PC compatible frequency	30-80 KHz (H) / 50-75 Hz (V) max. 1280 x 1024
Adjustable colour temperature	9300K / 6500K / 5800K / User
Video system	NTSC/PAL
Aspect ratio	4:3
VGA auto frequency correction	Yes
Number of speakers	x2
OSD control	Contrast, brightness, clock, phase, colour/tint, H-Position, V-Position, language, reset
Multi-language	English, French, German, Spanish, Italian, Chinese
Volume +/- Power ON/OFF	Yes
Power supply	12VDC, 4 amp
Voltage	AC100 - 240V 50 / 60 Hz
Power consumption	< 40W
Safety & EMC certifications	CE / FCC / ROHS
VESA standard mount	100 x 100 mm
Dimensions (without base)	435 (W) x 357 (H) x 55 (D) mm
Packing dimensions	480 (W) x 500 (H) x 165 (D) mm
Weight	Net: 5.9 kgs – Gross: 7.5 kgs
Accessories	Power supply, IEC lead, VGA cable, audio cable, user manual, remote

INTERFACE

Video In/Out (BNC type)	x1 In / x1 Out
S-Video	x1
VGA In	x1
Audio	x1 In / x1 Out

TEMPERATURE RANGE

Operating temperature	-10°C to 50 °C
Operating humidity	20 % - 70 %



deView Europe
 Falcon Court, Petre Road
 Clayton le Moors, Lancashire
 BB5 5JZ, United Kingdom
 Phone: +44 (0) 1254 302 490
 Email: sales@devieweurope.com

Fax: +44 (0) 1254 302 491
 Web: www.devieweurope.com