

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ




T: +44 (0) 1254 302490

F: +44 (0) 1254 302491










E: sales@deviueurope.com

Web: www.deviueurope.com

ECO domes

Product image	Part code	Description
	MD3CP12H4V9IT	3" (76mm) dome, indoor use, colour camera, 500 TVL, 1/3" format CCD, 1.2 lux @ F1.6, 4-9mm lens, 12VDC, ivory housing, tinted bubble
	MD3CP12H4V9BT	3" (76mm) dome, indoor use, colour camera, 500 TVL, 1/3" format CCD, 1.2 lux @ F1.6, 4-9mm lens, 12VDC, black housing, tinted bubble
	MD-QIP	Quick installation pipe

3" retail domes

Product image	Part code	Description
	MD3SP604V9IT NEW	3" (76mm) dome, indoor use, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 4-9mm lens, 12VDC, ivory housing, tinted bubble (replaces MD3CP12H4V9I / IT & MD3SP603V9IT)
	MD3SP604V9M NEW	3" (76mm) dome, indoor use, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 4-9mm lens, 12VDC, ivory housing, mirrored bubble (replaces MD3SP603V9M)
	MD3SP604V9BT NEW	3" (76mm) dome, indoor use, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 4-9mm lens, 12VDC, ivory housing, tinted bubble (replaces MD3CP12H4V9B / BT & MD3SP603V9BT)
	MD3SP603V9IT	3" (76mm) dome, indoor use, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 3-9mm lens, 12VDC, ivory housing, tinted bubble
	MD3SP603V9M	3" (76mm) dome, indoor use, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 3-9mm lens, 12VDC, ivory housing, mirrored bubble
	MD3SP603V9BT	3" (76mm) dome, indoor use, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 3-9mm lens, 12VDC, black housing, tinted bubble
	MD-QIP	Quick installation pipe
	SVC-CABLE	Service cable
	MD3-MDH-M	3" (76mm) dome, dummy camera, ivory housing, mirrored bubble
	MD3-MDH-I	3" (76mm) dome, dummy camera, ivory housing, tinted bubble
	MD3-MDHBT	3" (76mm) dome, dummy camera, black housing, tinted bubble

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ

T: +44 (0) 1254 302490

F: +44 (0) 1254 302491

E: sales@deviueurope.com

Web: www.deviueurope.com

4" retail domes

Product image	Part code	Description
	MD4SP603V9	4" (102mm) dome, indoor use, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, ivory housing, clear bubble
	MD4SP603V9B	4" (102mm) dome, indoor use, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, black housing, clear bubble
	MD4SPWD3V9	4" (102mm) dome, indoor use, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, ivory housing, clear bubble
	MD4SPWD3V9B	4" (102mm) dome, indoor use, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, black housing, clear bubble
	MD-QIP	Quick installation pipe
	MD4-RMKI	Recess mount accessory for the MD4 mini domes
	BKPCWM	Pendant mount bracket for the MD4 mini domes (use in conjunction with MD4-PCI)
	MD4-PCI	Pendant cap for the MD4 mini domes (use in conjunction with BKPCWM)
	MD4-WMI	Wall mount accessory for the MD4 mini domes
	MD4-CMI	Corner mount accessory for the MD4 mini domes
	SVC-CABLE	Service cable
	MD4-MDH	4" (102mm) dome, dummy camera, ivory housing, clear bubble




Micro domes

Product image	Part code	Description
	VDM2CP12H36C	Micro dome, indoor/outdoor use, colour camera, 520 TVL, 1/3" format CCD, 0.2 lux @ F1.2, 3.6mm lens, 12VDC, chrome housing, clear bubble
	VDM2DP12H36CL	Micro dome, indoor/outdoor use, day/night camera, IR Leds, 520 TVL, 1/3" format CCD, 0.0 lux @ F1.2 with IR Leds ON, 3.6mm lens, 12VDC, chrome housing, clear bubble
	VDM2-ASMAC	Angled surface mount adaptor
	VDM2-FSMAC	Flat surface mount adaptor



deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ

T: +44 (0) 1254 302490 F: +44 (0) 1254 302491 E: sales@devieweurope.com Web: www.devieweurope.com

Polycarbonate vandal domes

Product image	Part code	Description
	VDP25SP604V9 NEW	Polycarbonate dome, indoor/outdoor use, surface/flush mount, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 4-9mm lens, 12VDC only, built to IP66, impact protection >IK10+3 (replaces VDP25CP12H4V9)
	VDP20SP603V9	Polycarbonate dome, indoor/outdoor use, surface/flush mount, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+
	VDP20SP609V22	Polycarbonate dome, indoor/outdoor use, surface/flush mount, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 9-22mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+
	VDP20TP603V9	Polycarbonate dome, indoor/outdoor use, surface/flush mount, true day/night camera, 600 TVL, 1/3" format CCD, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+
	VDP20SPWD3V9	Polycarbonate dome, indoor/outdoor use, surface/flush mount, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+
	VDP20SPWD9V22	Polycarbonate dome, indoor/outdoor use, surface/flush mount, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 9-22mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+
	VDP20TPWD3V9	Polycarbonate dome, indoor/outdoor use, surface/flush mount, true day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+
	D2-CPM	Corner mount accessory for VDP20 series domes
	BKPCWM	Swan neck bracket for the VDP20 series domes (use in conjunction with VP-PCI)
	VP-PCI	Pendant cap for the VDP20 series domes (use in conjunction with BKPCWM)
	SVC-CABLE	Service cable
	VD-HTR	Heater kit for the VDP20 domes with 600 TVL camera modules
	VD-WDHTR	Heater kit for the VDP20 domes with Pixim Seawolf camera modules

Aluminium vandal domes

Product image	Part code	Description
	VDM25SP603V9 NEW	Aluminium dome, indoor/outdoor use, surface/flush mount, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM25SP609V22 NEW	Aluminium dome, indoor/outdoor use, surface/flush mount, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 9-22mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM25TP603V9 NEW	Aluminium dome, indoor/outdoor use, surface/flush mount, true day/night camera, 600 TVL, 1/3" format CCD, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM25SPWD3V9 NEW	Aluminium dome, indoor/outdoor use, surface/flush mount, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM25SPWD9V22 NEW	Aluminium dome, indoor/outdoor use, surface/flush mount, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 9-22mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM25TPWD3V9 NEW	Aluminium dome, indoor/outdoor use, surface/flush mount, true day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	SVC-CABLE	Service cable
	VD-HTR	Heater kit for the VDM25 domes with 600 TVL camera modules
	VD-WDHTR	Heater kit for the VDM25 domes with Pixim Seawolf camera modules

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ

T: +44 (0) 1254 302490

F: +44 (0) 1254 302491

E: sales@devieweurope.com

Web: www.devieweurope.com

Infrared and low-light domes

Product image	Part code	Description
	D411-DP12H33V12 LIMITED STOCK, ON DEMAND ONLY	Aluminium vandal dome, indoor/outdoor use, surface mount, software day/night, 540 TVL (day), 560 TVL (night), 1/3" format CCD, 3.3-12mm lens, 12VDC, built to IP66
	D411-TP12H33V12	Aluminium vandal dome, indoor/outdoor use, surface mount, true day/night, 540 TVL (day), 580 TVL (night), 1/3" format CCD, 0.0005 lux with SENS-UP, 3.3-12mm lens, 12VDC, built to IP66
	D411-TP22H33V12	Aluminium vandal dome, indoor/outdoor use, surface mount, true day/night, 540 TVL (day), 580 TVL (night), 1/3" format CCD, 0.0005 lux with SENS-UP, 3.3-12mm lens, 12VDC/24VAC, built to IP66
	D411-TP22H33V12L	Aluminium vandal dome, indoor/outdoor use, surface mount, true day/night, 540 TVL (day), 580 TVL (night), 1/3" format CCD, IR Leds, 0.00 lux @ F1.2, 3.3-12mm lens, 12VDC/24VAC, built to IP66
	D411-TP22H33V12LHTR	Aluminium vandal dome, indoor/outdoor use, surface mount, true day/night, 540 TVL (day), 580 TVL (night), 1/3" format CCD, IR Leds, 0.00 lux @ F1.2, 3.3-12mm lens, 12VDC/24VAC, built-in heater kit, built to IP66
	D411-TP22H33V12LWD	Aluminium vandal dome, indoor/outdoor use, surface mount, true day/night, Pixim Seawolf sensor, WDR, IR Leds, 0.00 lux @ F1.2, 3.3-12mm, 12VDC/24VAC, built to IP66, built-in heater kit
	D410-WMB	Wall Mount Bracket for D411/D410 Series

Prison domes

Product image	Part code	Description
	VDM15DP22H29V10I AVAILABLE WHILST STOCKS LAST	Aluminium vandal dome, indoor/outdoor use, surface/flush mount, software day/night camera, 540 TVL (day), 570 TVL (night), 1/3" format CCD, 0.65 lux @ F1.2, 2.9-10mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM15DP22H9V22I AVAILABLE WHILST STOCKS LAST	Aluminium vandal dome, indoor/outdoor use, surface/flush mount, software day/night camera, 540 TVL (day), 570 TVL (night), 1/3" format CCD, 0.65 lux @ F1.2, 9-22mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM15TP22H29V10I AVAILABLE WHILST STOCKS LAST	Aluminium vandal dome, indoor/outdoor use, surface/flush mount, true day/night camera, 540 TVL (day), 570 TVL (night), 1/3" format CCD, 0.25 lux @ F1.2, 2.9-10mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM15DP22H29V10WDI AVAILABLE WHILST STOCKS LAST	Aluminium vandal dome, indoor/outdoor use, surface/flush mount, software day/night camera, >504 TVL, Pixim Orca sensor, WDR, 0.95 lux @ F1.2, 2.9-10mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM15DP22H9V22WDI AVAILABLE WHILST STOCKS LAST	Aluminium vandal dome, indoor/outdoor use, surface/flush mount, software day/night camera, >504 TVL, Pixim Orca sensor, WDR, 0.95 lux @ F1.2, 9-22mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM15-CMB AVAILABLE WHILST STOCKS LAST	Corner mount bracket for VDM15 domes
	VDM15-CMBT AVAILABLE WHILST STOCKS LAST	Corner mount bracket with top plate for VDM15 domes
	SVC-CABLE	Service cable

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ

T: +44 (0) 1254 302490 F: +44 (0) 1254 302491 E: sales@deviueurope.com Web: www.deviueurope.com

Speed domes

Product image	Part code	Description
1) Choose the camera module		
	PDECP18	Colour camera, 480 TVL, 18x zoom, 1.5 Lux
	PDETP18	True day/night camera, 480 TVL, 18x zoom, 0.7 Lux
	PDETP26	True day/night camera, 480 TVL, 26x zoom, 1.0 Lux
	PDETP36	True day/night camera, 540 TVL, 36x zoom, 0.1 Lux
	PDECP22 NEW AVAILABLE QUARTER 2	Software day/night camera, 560 TVL, 22x zoom (replaces PDECP18)
	PDETP22 NEW AVAILABLE QUARTER 2	True day/night camera, 560 TVL, 22x zoom (replaces PDETP18 & PDETP26)
	PDETP35 NEW AVAILABLE QUARTER 2	True day/night camera, 560 TVL, 35x zoom (replaces PDETP36)
2) Choose the housing		
	PDHIR	Indoor recessed ceiling mount housing
	PDHIP	Indoor housing
	PDHEP	Outdoor housing
3) Choose the mounting accessories		
	PDBPMB25	Indoor/outdoor pendant mount bracket 1.5" NPT
	PDBWMB	Indoor/outdoor wall mount
	PDBCMA	Indoor/outdoor corner mount (use in conjunction with PDWMB)
	PDBPMA	Indoor/outdoor pole mount (use in conjunction with PDWMB)
	PDBSWN	Swan neck bracket

Keyboard

Product image	Part code	Description
	AKBD	Control keyboard

Specialty cameras for banks

Product image	Part code	Description
	ATMPWD29-12V	ATM camera, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 2.9mm lens, 12VDC
	ATMPWD29	ATM camera, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 2.9mm lens, 12VDC/24VAC
	IW-29WD-12V	In-wall camera kit, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 2.9mm lens, 12VDC
	NPWD29	Name Plate camera, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 2.9mm lens, 12VDC/24VAC
	ATM-WINACC NEW	Adapter bracket for the ATMPWD29 for the Wincor ATM machines

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ

T: +44 (0) 1254 302490 F: +44 (0) 1254 302491 E: sales@deviueurope.com Web: www.deviueurope.com

Box cameras

Product image	Part code	Description
	CR3SP5423 AVAILABLE WHILST STOCKS LAST	Box camera, software day/night, 540 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 230VAC
	CH23PH AVAILABLE WHILST STOCKS LAST	Box camera, true day/night, >504 TVL (day), 570 TVL (night), Pixim Orca sensor, WDR, 0.3 lux @ F1.2, 230VAC
	CR3SP6022	Box camera, software day/night, 600 TVL, 1/3" format CCD, 12VDC/24VAC
	CR3SP6023 NEW AVAILABLE APRIL	Box camera, software day/night, 600 TVL, 1/3" format CCD, 230V (replaces CR3SP5423)
	CR3TP6022	Box camera, true day/night, 600 TVL, 1/3" format CCD, 12VDC/24VAC
	CR3TP6023 NEW AVAILABLE APRIL	Box camera, true day/night, 600 TVL, 1/3" format CCD, 230V (replaces CJ23PH)
 WDR	CO3TP6522	Box camera, true day/night, 650 TVL (day), 700 TVL (night), 1/3" format CCD, 0.01 lux @ F1.2, 12VDC/24VAC
	CO3TP6523	Box camera, true day/night, 650 TVL (day), 700 TVL (night), 1/3" format CCD, 0.01 lux @ F1.2, 230 VAC
	CR3SPWD22	Box camera, software day/night, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 12VDC/24VAC
	CR3SPWD23	Box camera, software day/night, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 230V
	TV3X0310D	Senko "Pro" lens, 3-8.5mm, F1.0 DC Auto-iris
	TV4X2812D	Senko "Pro" lens, 2.8-12mm, F1.2 DC Auto-iris
	TV7X7513D	Senko "Pro" lens, 7.5-50mm, F1.3 DC Auto-iris
	BK5	Camera bracket, metal construction
	HAM-METRO230	Fully cable managed housing, built to IP67, aluminium construction, built-in heater, 230V
	HAM-METROLV	Fully cable managed housing, built to IP67, aluminium construction, built-in heater, 12VDC/24VAC
	HAM-POLEMOUNT	Polet mount accessory for the HAM-METRO230 and HAM-METROLV

IR lamps

Product image	Part code	Description
	HAY-IR-30/90 NEW	LED infrared illuminator 30m at 90 degrees
	HAY-IR-50/60 NEW	LED infrared illuminator 50m at 60 degrees
	HAY-IR-70/30 NEW	LED infrared illuminator 70m at 30 degrees
	HAY-METRO-IR-BKT1 NEW	1x IR bracket for HAM-METRO housing
	HAY-METRO-IR-BKT2 NEW	2x IR brackets for HAM-METRO housing
	HAY-IR-BKT NEW	IR single wall mount bracket

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ

T: +44 (0) 1254 302490

F: +44 (0) 1254 302491

E: sales@devieweurope.com

Web: www.devieweurope.com

Bullet cameras

Product image	Part code	Description
	BTP12H37V12L	Bullet camera, indoor/outdoor use, true day/night, 550 TVL, 1/3" format CCD, IR Leds, 0.0 lux, IR distance up to 40m, 3.7-12mm lens, 12VDC, built to IP65

LCD monitors

Product image	Part code	Description
	LCD-150TK	LCD 15" (38cm), metal case and glass front, 1024x768 resolution, 8ms response time, 500:1 contrast ratio, 270 cd/m2 brightness, UK & Euro plug, 1 x BNC In, 1x BNC Out, 1x VGA, IR Remote control
	LCD-170TK	LCD 17" (43cm), metal case and glass front, 1280x1024 resolution, 6ms response time, 800:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 1x BNC In, 1x BNC Out, 1x VGA, IR Remote control
	LCD-190TK	LCD 19" (48cm), metal case and glass front, 1280x1024 resolution, 6ms response time, 800:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 1x BNC In, 1x BNC Out, 1x VGA, IR Remote control
	LCD-150PC	LCD 15" (38cm), plastic casing, 1024x768 resolution, 8ms response time, 500:1 contrast ratio, 270cd/m2 brightness, UK & Euro plug, 1 x BNC In, 1x BNC Out, 1x VGA
	LCD-170PC	LCD 17" (43cm), plastic casing, 1280x1024 resolution, 8ms response time, 1000:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 1x BNC In, 1x BNC Out, 1x VGA, 1x HDMI
	LCD-190PC	LCD 19" (48cm), plastic casing, 1280x1024 resolution, 8ms response time, 1000:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 1x BNC In, 1x BNC Out, 1x VGA, 1x HDMI
	LCD-220PC	LCD 22" (56cm), 1280x1024 resolution, 5ms response time, 1000:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 1x VGA, 1x HDMI
	LCD-TESTMON	5.6" (14.2 cm) CCTV LCD test monitor with test pattern generator
	LA-27B	LCD bracket, wall mount, 3 axis, VESA 75/100, metal construction, black





LED monitors

Product image	Part code	Description
	LED-170PC NEW	LED monitor 17" (43cm), 1280x1024 resolution, 5ms response time, 10,000:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 1x VGA, 1x HDMI, black casing
	LED-190PC NEW	LED monitor 19" (48cm), 1280x1024 resolution, 5ms response time, 10,000:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 1x VGA, 1x HDMI, black casing
	LED-170PCV NEW	LED monitor 17" (43cm), 1280x1024 resolution, 5ms response time, 10,000:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 1x VGA, 1x HDMI, white casing
	LED-190PCV NEW	LED monitor 19" (48cm), 1280x1024 resolution, 5ms response time, 10,000:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 1x VGA, 1x HDMI, white casing
	LED-215PC NEW	LED 21.5" (54.6cm), 1920x1080 resolution, 5ms response time, 10,000:1 contrast ratio, 280 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 1x VGA, 1x HDMI
	LED-104TK NEW	LED monitor 10.4" (26.4cm), metal case and glass front, 800x600 resolution, 25ms response time, 500:1 contrast ratio, 250 cd/m2 brightness, UK & Euro plug, 1x BNC In, 1x VGA
	LED-170TK NEW	LED monitor 17" (43cm), metal case and glass front, 1280x1024 resolution, 5ms response time, 10,000:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 1x VGA, 1x HDMI
	LED-190TK NEW	LED monitor 19" (48cm), metal case and glass front, 1280x1024 resolution, 5ms response time, 10,000:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 1x VGA, 1x HDMI

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ

T: +44 (0) 1254 302490 F: +44 (0) 1254 302491 E: sales@devieweurope.com Web: www.devieweurope.com

Digital Video Recorders (prices subject to change)

Product image	Part code	Description
	ADVR-ECO-500	Eco DVR, 4 channels, 500 GB, H.264
	ADVR-4-500	DVR, 4 channels, 500 GB, H2.64
	ADVR4-1000	DVR, 4 channels, 1 TB, H2.64
	ADVR4-2000	DVR, 4 channels, 2 TB, H2.64
	ADVR8-500	DVR, 8 channels, 500 GB, H2.64
	ADVR8-1000	DVR, 8 channels, 1 TB, H2.64
	ADVR8-2000	DVR, 8 channels, 2 TB, H2.64
	ADVR16-500	DVR, 16 channels, 1 TB, H2.64
	ADVR16-1000	DVR, 16 channels, 1 TB, H2.64
	ADVR16-2000	DVR, 16 channels, 2 TB, H2.64
	ADVR16-4000	DVR, 16 channels, 4 TB, H2.64

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ


T: +44 (0) 1254 302490

F: +44 (0) 1254 302491






E: sales@deviueurope.com

Web: www.deviueurope.com

Video baluns

Product image	Part code	Description
	SJ-01C	Single channel passive video balun

Power supplies

Product image	Part code	Description
	HAY-PSUINLINE1A-UK	12VDC inline power supply, 1A, UK plug
	HAY-PSUINLINE1A-EU	12VDC inline power supply, 1A, Euro plug
	HAY-PSUINLINE3.5A-UK	12VDC inline power supply, 3.5A, UK plug
	HAY-PSUINLINE3.5A-EU	12VDC inline power supply, 3.5A, Euro plug
	HAY-PSUINLINE1A24-UK	24VAC inline power supply, 1A, UK plug
	HAY-PSUINLINE1A24-EU	24VAC inline power supply, 1A, bare ended
	HAY-PSUINLINE2A24-UK	24VAC inline power supply, 2A, UK plug
	HAY-PSUINLINE2A24-EU	24VAC inline power supply, 2A, bare ended
	DPS-ENC24VAC3.0UK	24VAC inline power supply, 3A, bare ended
	HAY-PSU412-5A	12VDC box power supply, 4x 12VDC outputs, 5A, metal case
	HAY-PSU412-10A	12VDC box power supply, 4x 12VDC outputs, 10A, metal case
	HAY-PSU912-5A	12VDC box power supply, 9x 12VDC outputs, 5A, metal case
	HAY-PSU912-10A	12VDC box power supply, 9x 12VDC outputs, 10A, metal case
	HAY-PSU1612-10A	12VDC box power supply, 16x 12VDC outputs, 10A, metal case
	HAY-PSU1612-20A	12VDC box power supply, 16x 12VDC outputs, 20A, metal case
	HAY-PSU4/1-1/4A24	24VAC box power supply, dual output, 4x 1A or 1x 4A, maximum output: 4A, metal case
	HAY-PSU8/1-1/8A24	24VAC box power supply, dual output, 8x 1A or 1x 8A, maximum output: 8A, metal case
	HAY-PSU4/2-2/4A24	24VAC box power supply, dual output, 4x 2A or 2x 4A, maximum output: 8A, metal case
	HAY-IP-24VPSU-1x4A	24VAC box power supply, 1 output, 4A, polycarbonate case, IP66
	HAY-IP-24VPSU-2x2A	24VAC box power supply, 2x 2A, polycarbonate case, IP66

deView Europe reserves the right to change specifications at any time without prior notice.