

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ





T: +44 (0) 1254 302490

F: +44 (0) 1254 302491








E: sales@deviweurope.com

Web: www.deviweurope.com

ECO domes

Product image	Part code	Description
	MD3CP12H4V9I	3" (76mm) dome, indoor use, colour camera, 500 TVL, 1/3" format CCD, 1.2 lux @ F1.6, 4-9mm lens, 12VDC, ivory housing, clear bubble
	MD3CP12H4V9IT	3" (76mm) dome, indoor use, colour camera, 500 TVL, 1/3" format CCD, 1.2 lux @ F1.6, 4-9mm lens, 12VDC, ivory housing, tinted bubble
	MD3CP12H4V9B	3" (76mm) dome, indoor use, colour camera, 500 TVL, 1/3" format CCD, 1.2 lux @ F1.6, 4-9mm lens, 12VDC, black housing, clear bubble
	MD3CP12H4V9BT	3" (76mm) dome, indoor use, colour camera, 500 TVL, 1/3" format CCD, 1.2 lux @ F1.6, 4-9mm lens, 12VDC, black housing, tinted bubble
	VDP25CP12H4V9I	Polycarbonate vandal dome, indoor/outdoor use, colour camera, 500 TVL, 1/3" format CCD, 1.2 lux @ F1.6, 4-9mm lens, 12VDC, built to IP66, impact protection >IK10+3
	MD-QIP	Quick installation pipe

3" retail domes

Product image	Part code	Description
	MD3DP12Q29V10I	3" (76mm) dome, indoor use, software day/night camera, 540 TVL (day), 570 TVL (night), 1/3" format CCD, 0.65 lux @ F1.2, 2.9-10mm lens, 12VDC, ivory housing, clear bubble, black inner liner
	MD3DP12Q29V10ICI	3" (76mm) dome, indoor use, software day/night camera, 540 TVL (day), 570 TVL (night), 1/3" format CCD, 0.65 lux @ F1.2, 2.9-10mm lens, 12VDC, ivory housing, clear bubble, ivory inner liner
	MD3SP603V9I NEW	3" (76mm) dome, indoor use, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 3-9mm lens, 12VDC, ivory housing, tinted bubble (replaces MD3DP12Q29V10I / MD3DP12Q29V10ITB)
	MD3SP603V9M NEW	3" (76mm) dome, indoor use, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 3-9mm lens, 12VDC, ivory housing, mirrored bubble (replaces MD3DP12Q29V10IM)
	MD3SP603V9BT NEW	3" (76mm) dome, indoor use, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 3-9mm lens, 12VDC, black housing, tinted bubble (replaces MD3DP12Q29V10BCB)
	MD-QIP	Quick installation pipe
	SVC-CABLE	Service cable
	MD3-MDH-M	3" (76mm) dome, dummy camera, ivory housing, mirrored bubble
	MD3-MDH-T	3" (76mm) dome, dummy camera, ivory housing, tinted bubble

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ











T: +44 (0) 1254 302490

F: +44 (0) 1254 302491

E: sales@deviueurope.com

Web: www.deviueurope.com

4" retail domes

Product image	Part code	Description
	MD4SP603V9 NEW	4" (102mm) dome, indoor use, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, ivory housing, clear bubble (replaces MD4DP22H29V10I)
	MD4SP603V9B NEW	4" (102mm) dome, indoor use, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, black housing, clear bubble (replaces MD4DP22H29V10B)
	MD4SPWD3V9 NEW	4" (102mm) dome, indoor use, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, ivory housing, clear bubble (replaces MD4DP22H29V10WDI)
	MD4SPWD3V9B NEW	4" (102mm) dome, indoor use, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, black housing, clear bubble
	MD-QIP	Quick installation pipe
	MD4-RMKI	Recess mount accessory for the MD4 mini domes
	BKPCWM	Pendant mount bracket for the MD4 mini domes (use in conjunction with MD4-PCI)
	MD4-PCI	Pendant cap for the MD4 mini domes (use in conjunction with BKPCWM)
	MD4-WMI	Wall mount accessory for the MD4 mini domes
	MD4-CMI	Corner mount accessory for the MD4 mini domes
	SVC-CABLE	Service cable
	MD4-MDH	4" (102mm) dome, dummy camera, ivory housing, clear bubble

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ




T: +44 (0) 1254 302490

F: +44 (0) 1254 302491

E: sales@deviueurope.com

Web: www.deviueurope.com

Polycarbonate vandal domes

Product image	Part code	Description
	VDP20DP22H29V10I	Polycarbonate dome, indoor/outdoor use, surface/flush mount, software day/night camera, 540 TVL (day), 570 TVL (night), 1/3" format CCD, 0.65 lux @ F1.2, 2.9-10mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+
	VDP20DP22H9V22I	Polycarbonate dome, indoor/outdoor use, surface/flush mount, software day/night camera, 540 TVL (day), 570 TVL (night), 1/3" format CCD, 0.65 lux @ F1.2, 9-22mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+
	VDP20DP22H29V10WDI	Polycarbonate dome, indoor/outdoor use, surface/flush mount, software day/night camera, >504 TVL, Pixim Orca sensor, WDR, 0.95 lux @ F1.2, 2.9-10mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+
	VDP20DP22H9V22WDI	Polycarbonate dome, indoor/outdoor use, surface/flush mount, software day/night camera, >504 TVL, Pixim Orca sensor, WDR, 0.95 lux @ F1.2, 9-22mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+
	VDP20SP603V9 NEW	Polycarbonate dome, indoor/outdoor use, surface/flush mount, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+ (replaces VDP20DP22H29V10I)
	VDP20SP609V22 NEW	Polycarbonate dome, indoor/outdoor use, surface/flush mount, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 9-22mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+ (replaces VDP20DP22H9V22I)
	VDP20TP603V9 NEW	Polycarbonate dome, indoor/outdoor use, surface/flush mount, true day/night camera, 600 TVL, 1/3" format CCD, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+ (replaces VDP20TP22H29V10I)
	VDP20SPWD3V9 NEW	Polycarbonate dome, indoor/outdoor use, surface/flush mount, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+ (replaces VDP20DP22H29V10WDI)
	VDP20SPWD9V22 NEW	Polycarbonate dome, indoor/outdoor use, surface/flush mount, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 9-22mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+ (replaces VDP20DP22H9V22WDI)
	VDP20TPWD3V9 NEW	Polycarbonate dome, indoor/outdoor use, surface/flush mount, true day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+ (replaces VDP20TP22H29V10WDI)
	D2-CPM	Corner mount accessory for VDP20 series domes
	BKPCWM	Swan neck bracket for the VDP20 series domes (use in conjunction with VP-PCI)
	VP-PCI	Pendant cap for the VDP20 series domes (use in conjunction with BKPCWM)
	SVC-CABLE	Service cable

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ


T: +44 (0) 1254 302490

F: +44 (0) 1254 302491




E: sales@deviweurope.com

Web: www.deviweurope.com

Aluminium vandal domes

Product image	Part code	Description
	VDM25SP603V9 NEW (FROM OCTOBER)	Aluminium dome, indoor/outdoor use, surface/flush mount, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM25SP609V22 NEW (FROM OCTOBER)	Aluminium dome, indoor/outdoor use, surface/flush mount, software day/night camera, 600 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 9-22mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM25TP603V9 NEW (FROM OCTOBER)	Aluminium dome, indoor/outdoor use, surface/flush mount, true day/night camera, 600 TVL, 1/3" format CCD, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM25SPWD3V9 NEW (FROM OCTOBER)	Aluminium dome, indoor/outdoor use, surface/flush mount, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM25SPWD9V22 NEW (FROM OCTOBER)	Aluminium dome, indoor/outdoor use, surface/flush mount, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 9-22mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM25TPWD3V9 NEW (FROM OCTOBER)	Aluminium dome, indoor/outdoor use, surface/flush mount, true day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 3-9mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3

Infrared and low-light domes

Product image	Part code	Description
	D411-DP12H33V12	Aluminium vandal dome, indoor/outdoor use, surface mount, software day/night, 540 TVL (day), 560 TVL (night), 1/3" format CCD, 3.3-12mm lens, 12VDC, built to IP66
	D411-TP12H33V12	Aluminium vandal dome, indoor/outdoor use, surface mount, true day/night, 540 TVL (day), 580 TVL (night), 1/3" format CCD, 0.0005 lux with SENS-UP, 3.3-12mm lens, 12VDC, built to IP66
	D411-TP22H33V12	Aluminium vandal dome, indoor/outdoor use, surface mount, true day/night, 540 TVL (day), 580 TVL (night), 1/3" format CCD, 0.0005 lux with SENS-UP, 3.3-12mm lens, 12VDC/24VAC, built to IP66
	D411-TP22H33V12L	Aluminium vandal dome, indoor/outdoor use, surface mount, true day/night, 540 TVL (day), 580 TVL (night), 1/3" format CCD, IR Leds, 0.00 lux @ F1.2, 3.3-12mm lens, 12VDC/24VAC, built to IP66
	D411-TP22H33V12LHTR	Aluminium vandal dome, indoor/outdoor use, surface mount, true day/night, 540 TVL (day), 580 TVL (night), 1/3" format CCD, IR Leds, 0.00 lux @ F1.2, 3.3-12mm lens, 12VDC/24VAC, built-in heater kit, built to IP66
	D410-TP22H33V12LWDR	Aluminium vandal dome, indoor/outdoor use, surface mount, true day/night, 480 TVL, Pixim Orca sensor, WDR, IR Leds, 0.00 lux @ F1.2, 3.3-12mm, 12VDC/24VAC, built to IP66
	D411-TP22H33V12LWD NEW	Aluminium vandal dome, indoor/outdoor use, surface mount, true day/night, Pixim Seawolf sensor, WDR, IR Leds, 0.00 lux @ F1.2, 3.3-12mm, 12VDC/24VAC, built to IP66, built-in heater kit (replaces D410-TP22H33V12LWDR)
	D410-WMB	Wall Mount Bracket for D411/D410 Series

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ





T: +44 (0) 1254 302490

F: +44 (0) 1254 302491

E: sales@deviueurope.com

Web: www.deviueurope.com

Prison domes

Product image	Part code	Description
	VDM15DP22H29V10I	Aluminium vandal dome, indoor/outdoor use, surface/flush mount, software day/night camera, 540 TVL (day), 570 TVL (night), 1/3" format CCD, 0.65 lux @ F1.2, 2.9-10mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM15DP22H9V22I	Aluminium vandal dome, indoor/outdoor use, surface/flush mount, software day/night camera, 540 TVL (day), 570 TVL (night), 1/3" format CCD, 0.65 lux @ F1.2, 9-22mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM15TP22H29V10I	Aluminium vandal dome, indoor/outdoor use, surface/flush mount, true day/night camera, 540 TVL (day), 570 TVL (night), 1/3" format CCD, 0.25 lux @ F1.2, 2.9-10mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM15DP22H29V10WDI	Aluminium vandal dome, indoor/outdoor use, surface/flush mount, software day/night camera, >504 TVL, Pixim Orca sensor, WDR, 0.95 lux @ F1.2, 2.9-10mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM15DP22H9V22WDI	Aluminium vandal dome, indoor/outdoor use, surface/flush mount, software day/night camera, >504 TVL, Pixim Orca sensor, WDR, 0.95 lux @ F1.2, 9-22mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	VDM15TP22H29V10WDI	Aluminium vandal dome, indoor/outdoor use, surface/flush mount, true day/night camera, >504 TVL (day), 570 TVL (night), Pixim Orca sensor, WDR, 0.42 lux @ F1.2, 2.9-10mm lens, 12VDC/24VAC, built to IP66, impact protection >IK10+3
	  	VDM15-CMB
VDM15-CMBT		Corner mount bracket with top plate for VDM15 domes
SVC-CABLE		Service cable
VD-FT922		Focus tool for the 9-22mm VDM15 camera modules

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ











T: +44 (0) 1254 302490

F: +44 (0) 1254 302491


E: sales@deviueurope.com

Web: www.deviueurope.com


Speed Domes

Product image	Part code	Description
1) Choose the camera module		
	PDECP18	Colour camera, 480 TVL, 18x zoom, 1.5 Lux
	PDETP18	True day/night camera, 480 TVL, 18x zoom, 0.7 Lux
	PDETP26	True day/night camera, 480 TVL, 26x zoom, 1.0 Lux
	PDETP36	True day/night camera, 540 TVL, 36x zoom, 0.1 Lux
	PDECP22 NEW (AVAILABILITY TBC)	Software day/night camera, 560 TVL, 22x zoom (replaces PDECP18)
	PDETP22 NEW (AVAILABILITY TBC)	True day/night camera, 560 TVL, 22x zoom (replaces PDETP18 & PDETP26)
	PDETP35 NEW (AVAILABILITY TBC)	True day/night camera, 560 TVL, 35x zoom (replaces PDETP36)
2) Choose the housing		
  	PDHIR	Indoor recessed ceiling mount housing
	PDHIP	Indoor housing
	PDHEP	Outdoor housing
3) Choose the mounting accessories		
    	PDBPMB25	Indoor/outdoor pendant mount bracket 1.5" NPT
	PDBWMB	Indoor/outdoor wall mount
	PDBCMA	Indoor/outdoor corner mount (use in conjunction with PDWMB)
	PDBPMA	Indoor/outdoor pole mount (use in conjunction with PDWMB)
	PDBSWN	Swan neck bracket

Keyboard

Product image	Part code	Description
	AKBD	Control keyboard

ATM cameras

Product image	Part code	Description
	ATMPWD29-12V NEW	ATM camera, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 2.9mm lens, 12VDC
	ATMPWD29 NEW	ATM camera, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 2.9mm lens, 12VDC/24VAC
	IW-29WD-12V NEW	In-wall camera kit, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 2.9mm lens, 12VDC

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ


T: +44 (0) 1254 302490

F: +44 (0) 1254 302491









E: sales@deviueurope.com

Web: www.deviueurope.com

Nameplate camera

Product image	Part code	Description
	NPWD29 NEW	Name Plate camera, software day/night camera, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 2.9mm lens, 12VDC/24VAC

Box cameras

Product image	Part code	Description	
	CR3SP5422	Box camera, software day/night, 540 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 12VDC/24VAC	
	CR3SP5423	Box camera, software day/night, 540 TVL, 1/3" format CCD, 0.3 lux @ F1.2, 230VAC	
	CJ22PH	Box camera, true day/night, 540 TVL (day), 570 TVL (night), 1/3" format CCD, 0.1 lux @ F1.2, 12VDC/24VAC	
	CJ23PH	Box camera, true day/night, 540 TVL (day), 570 TVL (night), 1/3" format CCD, 0.1 lux @ F1.2, 230VAC	
		CH22PH	Box camera, true day/night, >504 TVL (day), 570 TVL (night), Pixim Orca sensor, WDR, 0.3 lux @ F1.2, 12VDC/24VAC
		CH23PH	Box camera, true day/night, >504 TVL (day), 570 TVL (night), Pixim Orca sensor, WDR, 0.3 lux @ F1.2, 230VAC
	CR3SP6022 NEW	Box camera, software day/night, 600 TVL, 1/3" format CCD, 12VDC/24VAC (replaces CR3SP5422)	
	CR3SP6023 NEW (AVAILABILITY TBC)	Box camera, software day/night, 600 TVL, 1/3" format CCD, 230V (replaces CR3SP5423)	
	CR3TP6022 NEW	Box camera, true day/night, 600 TVL, 1/3" format CCD, 12VDC/24VAC (replaces CJ22PH)	
	CR3TP6023 NEW (AVAILABILITY TBC)	Box camera, true day/night, 600 TVL, 1/3" format CCD, 230V (replaces CJ23PH)	
		CQ3TP6522	Box camera, true day/night, 650 TVL (day), 700 TVL (night), 1/3" format CCD, 0.01 lux @ F1.2, 12VDC/24VAC
		CQ3TP6523	Box camera, true day/night, 650 TVL (day), 700 TVL (night), 1/3" format CCD, 0.01 lux @ F1.2, 230 VAC
		CR3SPWD22 NEW	Box camera, software day/night, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 12VDC/24VAC
		CR3SPWD23 NEW	Box camera, software day/night, 690 HTVL, Pixim Seawolf sensor, WDR, 0.1 lux @ F1.2, 230V
	TV4X2812D	Senko "Pro" lens, 2.8-12mm, F1.2 DC Auto-iris	
	TV7X7513D	Senko "Pro" lens, 7.5-50mm, F1.3 DC Auto-iris	
		BK5	Camera bracket, metal construction
			HAM-METRO230
	HAM-METROLV		Fully cable managed housing, built to IP67, aluminium construction, built-in heater, 12VDC/24VAC

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ


T: +44 (0) 1254 302490

F: +44 (0) 1254 302491




E: sales@deviueurope.com

Web: www.deviueurope.com

Bullet cameras

Product image	Part code	Description
	BTP12H37V12L	Bullet camera, indoor/outdoor use, true day/night, 550 TVL, 1/3" format CCD, IR Leds, 0.0 lux, IR distance up to 40m, 3.7-12mm lens, 12VDC, built to IP65



LCD monitors

Product image	Part code	Description
	LCD-104TK	LCD 10.4" (26.4cm), metal case and glass front, 640x480 resolution, 300:1 contrast ratio, 350 cd/m2 brightness, UK & Euro plug, 1 x BNC and 1x VGA
	LCD-150TK	LCD 15" (38cm), metal case and glass front, 1024x768 resolution, 12ms response time, 500:1 contrast ratio, 250cd/m2 brightness, UK & Euro plug, 1 x BNC In, 1x BNC Out, 1x VGA, IR Remote control
	LCD-170TK	LCD 17" (43cm), metal case and glass front, 1280x1024 resolution, 12ms response time, 500:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 1x BNC In, 1x BNC Out, 1x VGA, IR Remote control
	LCD-190TK	LCD 19" (48cm), metal case and glass front, 1280x1024 resolution, 8ms response time, 800:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 1x BNC In, 1x BNC Out, 1x VGA, IR Remote control
	LCD-170TKHDMI	LCD 17" (43cm), metal case and glass front, 1280x1024 resolution, 8ms response time, 500:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 1x VGA, 1x HDMI, IR Remote control
	LCD-190TKHDMI	LCD 19" (48cm), metal case and glass front, 1280x1024 resolution, 8ms response time, 500:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 1x VGA, 1x HDMI, IR Remote control
	LCD-150PC	LCD 15" (38cm), "ECO" range, 1024x768 resolution, 8ms response time, 500:1 contrast ratio, 300cd/m2 brightness, UK & Euro plug, 1 x BNC In, 1x BNC Out, 1x VGA
	LCD-170PC	LCD 17" (43cm), "ECO" range, 1280x1024 resolution, 8ms response time, 500:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 1x BNC In, 1x BNC Out, 1x VGA
	LCD-190PC	LCD 19" (48cm), "ECO" range, 1280x1024 resolution, 8ms response time, 500:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 1x BNC In, 1x BNC Out, 1x VGA
	LCD-170PCHDMI	LCD 17" (43cm), "ECO+" range, 1280x1024 resolution, 8ms response time, 500:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 1x VGA, 1x HDMI
	LCD-190PCHDMI	LCD 19" (48cm), "ECO+" range, 1280x1024 resolution, 8ms response time, 500:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 1x VGA, 1x HDMI
	LA-27B	LCD bracket, wall mount, 3 axis, VESA 75/100, metal construction, black





deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ

T: +44 (0) 1254 302490 F: +44 (0) 1254 302491 E: sales@deviueurope.com Web: www.deviueurope.com


LED Monitors

Product image	Part code	Description
	LED-170PC NEW	LED monitor 17" (43cm), 1280x1024 resolution, 5ms response time, 10,000:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 2x VGA, 1x HDMI, black casing
	LED-190PC NEW	LED monitor 19" (48cm), 1280x1024 resolution, 5ms response time, 10,000:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 2x VGA, 1x HDMI, black casing
	LED-170PCW NEW	LED monitor 17" (43cm), 1280x1024 resolution, 5ms response time, 10,000:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 2x VGA, 1x HDMI, white casing
	LED-190PCW NEW	LED monitor 19" (48cm), 1280x1024 resolution, 5ms response time, 10,000:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 2x VGA, 1x HDMI, white casing
	LED-170TK NEW	LED monitor 17" (43cm), metal case and glass front, 1280x1024 resolution, 5ms response time, 10,000:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 2x VGA, 1x HDMI
	LED-190TK NEW	LED monitor 19" (48cm), metal case and glass front, 1280x1024 resolution, 5ms response time, 10,000:1 contrast ratio, 300 cd/m2 brightness, UK & Euro plug, 2x BNC In, 2x BNC Out, 2x VGA, 1x HDMI

Digital Video Recorders

Product image	Part code	Description
	ADVR-ECO-500	Eco DVR, 4 channels, 500 GB
	ADVR4-250	4 channel 250 GB H.264 DVR
	ADVR-4-500	4 channel 500 GB H.264 DVR
	ADVR4-1000	4 channel 1 TB H.264 DVR
	ADVR8-500	8 channel 500 GB H.264 DVR
	ADVR8-1000	8 channel 1 TB H.264 DVR
	ADVR8-2000	8 channel 2 TB H.264 DVR
	ADVR16-500	16 channel 500 GB H.264 DVR
	ADVR16-1000	16 channel 1 TB H.264 DVR
	ADVR16-2000	16 channel 2 TB H.264 DVR
	ADVR16-3000	16 channel 3 TB H.264 DVR

Video baluns

Product image	Part code	Description
	SJ-01C	Single channel passive video balun

deView Europe, Falcon Court, Petre Road, Clayton-le-Moors, Accrington, Lancashire, England, BB5 5JZ






T: +44 (0) 1254 302490

F: +44 (0) 1254 302491

E: sales@deviueurope.com

Web: www.deviueurope.com

Power supplies

Product image	Part code	Description
	HAY-PSUINLINE1A-UK	12VDC inline power supply, 1A, UK plug
	HAY-PSUINLINE1A-EU	12VDC inline power supply, 1A, Euro plug
	HAY-PSUINLINE3.5A-UK	12VDC inline power supply, 3.5A, UK plug
	HAY-PSUINLINE3.5A-EU	12VDC inline power supply, 3.5A, Euro plug
	HAY-PSUINLINE1A24-UK	24VAC inline power supply, 1A, UK plug
	HAY-PSUINLINE1A24-EU	24VAC inline power supply, 1A, Euro plug
	HAY-PSUINLINE2A24-UK	24VAC inline power supply, 2A, UK plug
	HAY-PSUINLINE2A24-EU	24VAC inline power supply, 2A, Euro plug
	DPS-ENC24VAC3.0UK	24VAC inline power supply, 3A, bare ended
	HAY-PSU412-5A	12VDC box power supply, 4x 12VDC outputs, 5A, metal case
	HAY-PSU412-10A	12VDC box power supply, 4x 12VDC outputs, 10A, metal case
	HAY-PSU912-5A	12VDC box power supply, 9x 12VDC outputs, 5A, metal case
	HAY-PSU912-10A	12VDC box power supply, 9x 12VDC outputs, 10A, metal case
	HAY-PSU612-10A	12VDC box power supply, 16x 12VDC outputs, 10A, metal case
	HAY-PSU4/1-1/4A24	24VAC box power supply, dual output, 4x 1A or 1x 4A, maximum output: 4A, metal case
	HAY-PSU8/1-1/8A24	24VAC box power supply, dual output, 8x 1A or 1x 8A, maximum output: 8A, metal case
	HAY-PSU4/2-2/4A24	24VAC box power supply, dual output, 4x 2A or 2x 4A, maximum output: 8A, metal case
	HAY-IP-24VPSU-1x4A	24VAC box power supply, 1 output, 4A, polycarbonate case, IP66

deView Europe reserves the right to change specifications at any time without prior notice.

Warranty:

Cameras/Monitors/DVRs: 3 years.

Power supplies/box camera housings/video baluns/lenses: 1 year.